



DWM



DWMW



DTX10-W

Information

1. Sharp stereo erect image over a wide field of view
2. 45° inclined and 360° rotatable binocular head with locked-in eyepiece. The left and right ocular-tube with diopter adjustment ±5dp
3. Three kind of 90° 1×/2×, 1×/3×, 2×/4×, DTX10/DTX20 is with knob rotation.
4. Power supply 110V/60HZ or 220V/50HZ
5. Product has CE approval
6. Illumination:
  - L1: Incident reflected halogen light 12V 10W; Transmitted halogen light 12V 10W, brightness is adjustable.
  - L2: Both incident and transmitted light with LED

Model	Eyepiece	Objective	Up & down Mechanism	Base/Working Stage
DSM	SWF10×	1X-2X, 1X-3X, 2X-4X	Arm curved style	Ø95mm White/Black working stage
				Fan plain base
DSM-W			Arm curved style	Ø95mm White/Black working stage
				Fan plain base
DTX10-W			Arm curved style	95mm White/Black working stage
				Fan plain base
DTX11-W			Arm curved style	95mm White/Black working stage
	Fan plain base			
DTX20-W	Arm curved style	95mm White/Black working stage		
		Fan high base		
DTX21	Pillar style	95mm Frosted glass		
		Fan high base		

Optional accessories WF5x, SWF10x, WF15x, WF20× Eyepiece; Ring light

Objective Magnification	Eyepiece								Working Distance (mm)
	WF5X		SWF10X		WF15X		WF20X		
	Magnification	Field of View (mm)	Magnification	Field of View (mm)	Magnification	Field of View (mm)	Magnification	Field of View (mm)	
1×	5×	20.0	10×	22.0	15×	15.0	20×	10.0	100
2×	10×	10.0	20×	11.0	30×	7.5	40×	6.5	
1×	5×	20.0	10×	22.0	15×	15.0	20×	10.0	100
3×	15×	7.0	15×	7.3	45×	5.0	60×	4.3	
2×	10×	10.0	20×	11.0	30×	7.5	40×	6.5	100
4×	20×	5.0	40×	5.5	60×	3.7	80×	3.2	



DTX11-W



DTX20-W



DTX21