

MiniTec™ Autoranging Digital MultiMeter

Rugged pocket design, 11 functions including Temperature, Capacitance and Frequency

Features:

- 4000 counts on large LCD with full function indication
- Measures AC/DC Voltage and Current, Resistance, Capacitance, Frequency and Temperature
- Temperature measurements to 1400°F (760°C)
- Duty Cycle, Continuity and Diode test
- Autoranging with manual range override
- Relative zero, Data Hold and Range Hold
- 10A fuse protection
- Overload protection and indication
- Auto power off saves battery life
- Includes protective rubber holster with stand, temperature probe (-40 to 482°F/-40 to 250°C) two 1.5V AAA batteries, and test leads



CAT II - 600V

Specifications	Ranges	Max Resolution	Basic Accuracy (%rdg)
DC Voltage:	400mV, 4V, 40V, 400V, 600V	0.1mV	±1.0%
AC Voltage:	400mV, 4V, 40V, 400V, 600V	0.1mV	±1.5%
AC Current:	400µA, 4000µA, 40mA, 400mA, 10A	0.1µA	±1.8%
DC Current:	400µA, 4000µA, 40mA, 400mA, 10A	0.1µA	±1.5%
Resistance (Ω):	400, 4k, 40k, 400k, 4M, 40MΩ	0.1Ω	±1.2%
Capacitance:	4nF, 40nF, 400nF, 4µF, 40µF, 200µF	0.001nF	±3.5%
Frequency (Hz):	10Hz to 10MHz	0.001Hz	±1.5%
Temperature:	0 to 1400°F (0 to 760°C)	1°	±3.0%
Duty Cycle:	0.1% to 99.9%	0.1%	±1.2%
Continuity:	Below 30Ω approx.		
Diode test:	Test current 0.3mA; Open circuit voltage 1.5V		
Power:	Two 1.5V AAA batteries		
Dimensions:	4.8 x 2.4 x 1.6" (122 x 61 x 40mm)		
Weight:	9.17oz (260g)		

Ordering Information:

MN26TAutoranging MiniTec™
MN26T-NISTAutoranging MiniTec™ with NIST Certificate
409992Vinyl pouch carrying case

EXTECH INSTRUMENTS CORPORATION
 285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
 Phone: 781-890-7440 • Fax: 781-890-7864
 ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



02/22/05 - R1