

Hand Multiplier

		Maximum Torque —			
		Input		Output	
Model	Item #	lbf.ft	N.m	lbf.ft	N.m
MTM-15	215026	170	231	1105	1500
MTM-27	215027	559	758	2000	2700

Model	Female Input Square Drive	Male Output Square Drive	Torque Multiplication Ratio
MTM-15	1/2"	3/4"	6.5:1
MTM-27	3/4"	1"	3.3:1

→ HEAD DIMENSIONS and WEIGHT

	Length		— Height		┌ Weight	
Model	in.	mm	in.	mm	lbs.	
MTM-14	6 1/3"	160	3 7/8"	97	5.7	
MTM-27	7 1/2"	190	4 1/3"	111	7.5	



MTM-15 Case Set

Multiplier Reaction Bar (L = 380mm) Reaction 90° Base Reaction 90° Bar Breakaway Adapter



MTM-27 Case Set

Multiplier Reaction Bar (L = 380mm) Reaction 90° Base Reaction 90° Bar

Accuracy better than \pm 5%.

Precision tightening for heavy duty fastening connections.

Constructed with quality steel and matted finish.

Commonly used in construction, heavy equipment & power generation industries.

Portable, compact and lightweight.

Torque Multiplication Ratio - low energy input with high torque output.

For operation in combination with a torque wrench.

Ideal for remote locations where no source of power is available.

Includes plastic case.