



Inner and Outer DC Block From 10 MHz to 26.5 GHz With 2.92mm Connectors

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	0.01		26.5	GHz
Impedance		50		Ohms
VSWR			1.35:1	
Insertion Loss			0.75	dB
Operating Voltage (DC)			200	Volts



Mechanical Specifications

Size	
Length	0.86 in [21.84 mm]
Width	0.5 in [12.7 mm]
Weight	0.0146 lbs [6.62 g]

Description	Connector	1 Connecto
Design Package Type		nner/Outer DC Block onnectorized
Configuration		

Description	Connector 1	Connector 2
Туре	2.92mm Male	2.92mm Female

Compliance Certifications (visit www.FairviewMicrowave.com for current

document)

RoHS Compliant
REACH Compliant


Yes

12/17/2015

Plotted and Other Data

Notes:

Typical Performance Data



Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Inner and Outer DC Block From 10 MHz to 26.5 GHz With 2.92mm Connectors from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link to obtain additional part information: Inner and Outer DC Block From 10 MHz to 26.5 GHz With 2.92mm Connectors SD3475

URL: https://www.fairviewmicrowave.com/inner-and-outer-dc-block-10-mhz-26.5-ghz-2.92mm-connectors-sd3475-p. aspx









STANDARD TOLERANCES
.X ±0.2
.XX ±0.1

.XX ±0.1 .XXX ±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].				
Inner and Outer DC Block From 10 MHz to 26.5 GHz With 2.92mm Connectors	DWG NO SD3475		CAGE CODE 3FKR5		
	CAD FILE 070716	SHEET	SCALE	≣ N/A	SIZE A