



Programmable DC Electronic Load

—150W-200W-300W Series



OVERVIEW

- HT8XXX load is a precision programmable DC electronic load controlled by a high-performance microprocessor. It uses 3.5-inch TFT true color LCD display with Chinese and English menu.
- Offers 4 basic working modes (CC/CV/CR/CW) and 10 functional modes.
- With comprehensive protection, over-heat protection, over-current protection, over-power protection, over-voltage protection, loop oscillation protection. HT8XXX series E-load supports RS232, LAN, USB and analog interfaces to fit your versatile solution and testing needs.

Test function

4 basic working modes CC/CV/CR/CW and 11 functional modes multiple extended function modes:

- Short test function
- DYNA dynamic test function
- OCP over current protection mode
- BATT battery mode
- EFFT load effect mode
- SWEEP dynamic frequency conversion scanning function
- TIMING _me measurement function
- OVP over voltage protection mode
- AUTO mode
- LIST function
- LED (HP8151 has no LED mode)

特性 (FEATURES)

- 500kHz high speed voltage, current sampling rate
- High precision voltage and current measurement
- Fast loop response speed and current slew rate
- Programmable single step up to 10μS
- Equipped with remote four-wire compensation
- Unique real-time display of current ripple and voltage ripple
- Real-time display of load power and resistance


应用 (APPLICATION)



Switching power supply



LED power supply



Cell phone battery charger




Cell phone charger




UPS



Vehicle electronics



Power battery pack



Fuse



■ SPECIFICATION

Model	HT8151		HT8151A		HT8151B		HT8201													
Inputvoltage	15V	150V	15V	150V	50V	500V	15V	150V												
Inputcurrent	3A	30A	3A	30A	1.5A	15A	3A	30A												
Inputpower			150W				200W													
Min.operation voltage	1.5V@30A		7.5V@15A		1.5V@30A															
Min risetime@FS current			10us																	
CV mode																				
Range	15V	150V	15V	150V	50V	500V	15V	150V												
Resolution	0.2mV	2m	0.2mV	2mV	0.7mV	7mV	0.2mV	2mV												
Accuracy	±(0.05%+0.025%FS)																			
CC mode																				
Range	3A	30A	3A	30A	1.5A	15A	3A	30A												
Resolution	0.04mA	0.4mA	0.04mA	0.4mA	0.02mA	0.2mA	0.04mA	0.4mA												
Accuracy	±(0.05%+0.05%FS)																			
CR mode																				
Range	0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ													
Resolution	16Bits																			
Accuracy	±0.1%																			
CW mode																				
Range	150W				200W															
Resolution	16Bits																			
Accuracy	± (0.1%+0.1%FS)																			
LED mode																				
bandwidth	-----		100kHz以上																	
Rd coefficient	-----		0.001~1																	
Dynamic mode																				
Ta & Tb	10uS~50s																			
Min.resolution	10us																			
Min. rise time	1.5A/us	1.5A/us		0.8A/us		1.5A/us														
Read-back voltage																				
Range	15V	150V	15V	150V	50V	500V	15V	150V												
Resolution	0.1mV	1mV	0.1mV	1mV	0.3mV	3mV	0.1mV	1mV												
Accuracy	±(0.025%+0.025%FS)																			
Read-back current																				
Range	3A	30A	3A	30A	1.5A	15A	3A	30A												
Resolution	0.02mA	0.2mA	0.02mA	0.2mA	0.01mA	0.1mA	0.02mA	0.2mA												
Accuracy	±(0.05%+0.05%FS)																			
Read-back Ripple																				
Range(R/I)	-----		150V/30A		500V/15A		150V/30A													
bandwidth	-----		10Hz~250kHz																	
Accuracy	±1%																			
Protection range																				
Over-powerprotection	158W						210W													
Over-currentprotection	32A				16A		32A													
Over-voltageprotection	158V				525V		158V													
Over-temperatureprotection	≈85°C																			
Specification																				
Dimension (D*W*H)	358mm*214mm*88mm																			
Gross Weight	3.8Kg																			



SPECIFICATION

Model	HT8201B		HT8301		HT8301B		HT8301C							
Inputvoltage	50V	500V	30V	150V	50V	500V	15V	150V						
Inputcurrent	1.5A	15A	3A	30A	1.5A	15A	6A	60A						
Inputpower	200W		300W											
Min.operation voltage	6.5V@15A		1V@30A		4V@15A		1.5V@60A							
Min.risetime@FS current	10us		30us		20us									
CV mode														
Range	50V	500V	30V	150V	50V	500V	15V	150V						
Resolution	0.7mV	7mV	0.2mV	2mV	0.7mV	7mV	0.2mV	2mV						
Accuracy	$\pm(0.05\%+0.05\%FS)$													
CC mode														
Range	1.5A	15A	3A	30A	1.5A	15A	6A	60A						
Resolution	0.02mA	0.2mA	0.04mA	0.4mA	0.02mA	0.2mA	0.09mA	0.9mA						
Accuracy	$\pm(0.05\%+0.05\%FS)$													
CR mode														
Range	0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ		0.1Ω~7.5kΩ							
Resolution	16Bits													
Accuracy	$\pm 0.1\%$													
CW mode														
Range	200W		300W											
Resolution	16Bits													
Accuracy	$\pm (0.1\%+0.1\%FS)$													
LED mode														
bandwidth	100kHz以上													
Rd coefficient	0.001~1													
Dynamic mode														
Ta & Tb	10us~50s													
Min.resolution	10us													
Min. rise time	0.8A/us	1.5A/us		0.8A/us		3A/us								
Read-back voltage														
Range	50V	500V	15V	150V	50V	500V	15V	150V						
Resolution	0.3mV	3mV	0.1mV	1mV	0.3mV	3mV	1mV	0.1mV						
Accuracy	$\pm(0.025\%+0.025\%FS)$													
Read-back current														
Range	1.5A	15A	3A	30A	1.5A	15A	6A	60A						
Resolution	0.01mA	0.1mA	0.02mA	0.2mA	0.01mA	0.1mA	0.04mA	0.4mA						
Accuracy	$\pm(0.05\%+0.05\%FS)$													
Read-back Ripple														
Range(R/I)	500V/15A		150V/30A		500V/15A		150V/60A							
bandwidth	10Hz~250kHz													
Accuracy	$\pm 1\%$													
Protection range														
Over-powerprotection	210W		315W											
Over-currentprotection	16A		32A		16A		63A							
Over-voltage protection	525V		158V		525V		158V							
Over-temperatureprotection	$\leq 85^{\circ}\text{C}$													
Specification														
Dimension (D*W*H)	358mm*214mm*88mm													
Gross Weight	3.8Kg													