

CITIZEN

High speed, high resolution, heavy duty printing

CL-S700 with 300dpi



Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

300 dpi Resolution

The CL-S703II is ideal for small labels with 2D matrix barcodes such as Datamatrix, DataBar, QR-Code and PDF417 or printing company logos and ids and CE or WEEE logos.

CL-S703II

Label, Industrial

Applications

- Healthcare
- Manufacturing
- Retail



High performance with easy access

TOMORROW'S PRINTING TODAY

CITIZEN

Specifications

Model	CL-S703II
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	300 dpi
Print Speed (maximum)	8 inches per second (200 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 to 5 inches (25.4 to 118.1 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 64 inches (6.35 to 1625.6 mm)
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT)
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 4-line back-lit graphic LCD

CL-S703II

Label, Industrial

Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- ENERGY STAR® compliant
- Recyclable packaging
- Basic peeler



Ingeniously designed for easy operation and reliability

Model	CL-S703II
Emulations (Languages)	Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Datamax® I-Class™ & DMX400™, Zebra® ZPL-II®, BASIC interpreter for data stream processing, Eltron®, EPL-2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	255 x 490 x 265 mm, 13.3 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0