# **Products for Industry**

Fume Hood

**LDS-N180S** 

Item Code : A000265 Model : LDS-N180S

Page Top

**Product Summary** 

Specifications

Same series products





# Fume Hood (LDS-N180S)

**Contact Us** 

Printing

### **Product Summary**

#### Fume hood with fixed exhaust air volume

#### Features of Fume Hood (LDS-N180S)

#### **Features**

Main unit is made of steel, chemical resistant powder coating applied; excellent fire resistance

#### **Features**

Non-asbestos, non-combustible veneer interior with excellent chemical and heat resistance

#### **Features**

Selectable work surface material

#### **Features**

Storage located in the lower base (not applicable to benchtop type)

#### **Features**

Equipped with multi-slit baffle to efficiently exhaust harmful gas in the fume hood

#### Features

Safety features include door drop prevention stopper, ventilator delay timer and exhaust blower activation monitor

#### **Features**

Outlets and switches are located at an easy operating height

#### **Features**

Selectable air speed meter, which digitally displays the front air speed and exhaust air volume (option)

### **Specifications**

#### **Specifications**

Item Code	A000265
Model	LDS-N180S
Exterior	Cool-milling steel, chemical-resistant baked paint finish
Interior	Non-asbestos, non-combustible decorative board (baffle plate: multi-slit type)
Working surface material	Ceramitite
Glass window	Reinforced glass, 6mm thickness, balance weight type
Water faucet	Single goose neck type, 1pc.
Outlet	AC115/ 220V with dual grounding wire (dropout prevention) 1pc.
Fluorescent lamp	40W 1pc
Safety feature	Door drop prevention stopper, ventilator delay timer, exhaust blower activation monitor
Option	Gas cock, LDX anemometer, LED lighting, safety mechanism (double wire door fall prevention mechanism)
Standard discharge air quantity	19m <sup>3</sup> /min
Static pressure	79Pa
External dimensions (W×D×H mm)	1800×750×2400mm
Power Source	AC115/ 220V
Weight	370kg

#### **Maintenance and warranty**

Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load) External dimensions do not include protrusions.

# Same series products





