

Products for Industry

Fume Hood (Benchtop type)

LDS-N120T

Item Code : A003037

Model : LDS-N120T

[Page Top](#)

[Product Summary](#)

[Specifications](#)

[Same series products](#)



Fume Hood (Benchtop type) (LDS-N120T)

[Contact Us](#)

[Printing](#)

Product Summary

Fume hood with fixed exhaust air volume

Features of Fume Hood (Benchtop type) (LDS-N120T)

Features

Main unit is made of steel, chemical resistant powder coating applied; excellent fire resistance

Features

Non-asbestos, non-combustible veneer interior with excellent chemical and heat resistance

Features

Selectable work surface material

Features

Storage located in the lower base (not applicable to benchtop type)

Features

Equipped with multi-slit baffle to efficiently exhaust harmful gas in the fume hood

Features

Safety features include door drop prevention stopper, ventilator delay timer and exhaust blower activation monitor

Features

Outlets and switches are located at an easy operating height

Features

Selectable air speed meter, which digitally displays the front air speed and exhaust air volume (option)

Specifications

Specifications

| | |
|---------------------------------|---|
| Item Code | A003037 |
| Model | LDS-N120T |
| Exterior | Cool-milling steel, chemical-resistant baked paint finish |
| Interior | Non-asbestos, non-combustible decorative board (baffle plate: multi-slit type) |
| Working surface material | Ceramitite |
| Glass window | Reinforced glass, 6mm thickness, balance weight type |
| Outlet | AC115/ 220V with dual grounding wire (dropout prevention) 1pc. |
| Fluorescent lamp | 32W 1pc |
| Safety feature | Door drop prevention stopper, ventilator delay timer, exhaust blower activation monitor |
| Option | LDX anemometer, LED lighting, safety mechanism (double wire door fall prevention mechanism) |
| Standard discharge air quantity | 12m ³ /min |
| Static pressure | 30Pa |
| External dimensions (W×D×H mm) | 1200×750×1550mm |
| Power Source | AC115/ 220V |
| Weight | 130kg |

Maintenance and warranty

Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load)

External dimensions do not include protrusions.

Same series products



Fume Hood (Air curtain type)
(LDS-N120SA)



Fume Hood (Low-ceiling type)
(LDS-N120SJ)



Fume Hood (LDS-N150S)

