

DISTRIBUTOR SITE

EN/中文/JP▼

Search

**PRODUCTS** 

INDUSTRY SOLUTIONS

**ABOUT US** 

**NEWS** 

FAQ



ŵ > PRODUCTS > Fully Automatic Strapping Machines > TP-702BP Mercury Transit with Press

# **PRODUCTS**

- Strapping Tools
- Semi-Auto Strapping Machines
- Automatic Strapping Machines
- Fully Automatic Strapping Machines
- Corrugated Strapping Machines
- Print Media Strapping Machines



DISTRIBUTOR SITE EN/中文/JP▼

Q Search

**PRODUCTS** 

INDUSTRY SOLUTIONS

ABOUT US

NEWS

FAQ

### **TP-702BP Mercury Transit with Press**



Mercury Transit TP-702BP is a fully automatic strapping machine with compression press for production and packaging lines. It is suitable for 5 mm, 6 mm, 9 mm, or 12 mm PP strapping. TP-702BP is the fastest and most reliable strapping machine for general applications on the market today.



#### **Features**

- · Robust & compact mechanical strapping head
- · With pneumatic press
- Waist-high auto strap feeding
- Free access to strap guides (patents registered)
- · Electronic tension control
- · Auto strap ejector
- · Hinged top plates
- Multiple strap function for single, double, continuous strapping, or transit mode
- Variable conveyor speed between 10 and 60 meters/minute
- Up and down stream interlock with complete plug connection
- · Easy bundle flow direction change
- Good to strap small package with minimum size 120 mm in width and 10 mm in height
- Adjustable table height between 800 mm and 900 mm

#### **Options**

- Siemens PLC
- Light tower with low strap sensor
- · Energy saving transit with auto sleep mode
- · Strapping in the center of the bundle
- Extension belt-driven table of 200 mm on upstream and downstream sides
- Lower adjustable table height (750 mm 900 mm)



DISTRIBUTOR SITE

EN/中文/JP▼

Search

**PRODUCTS** 

INDUSTRY SOLUTIONS

ABOUT US

NEWS

FAQ

### **Technical Data**

Strap Width	5 mm, 6 mm, 9 mm, or 12 mm
Tension Range	1-32 kg (for 5 mm, 6 mm, 9 mm) 1-55 kg (for 12mm)
Capacity	Up to 36 packages/minute (Cycle speed up to 65 cycles/minute)
Weight	250 kg
Pneumatic Source	6 bar
Air Consumption	7.5 liter/cycle
Electrical Requirements	110V, 220V, 230V, 240V 50/60Hz 1PH 220V, 380V, 400V, 415V 50/60Hz 3PH

## ALL PRODUCTS ARE WELL MADE BY OUR ISO 9001 CERTIFIED FACTORY IN TAIWAN, WITH PRIDE.

ம் 15F-1, NO. 17, SEC. 1, CHENGDE ROAD, TAIPEI 103, TAIWAN ☑ transpak@tran 🚓

